


Leading manufacturer of precast and pre-stressed concrete joists

Our pre-cast concrete joists have been used by the building industry for three decades. Architects, engineers, builders, and developers favour our products because of its unmatched quality in the Philippines.

Our growth and success is a direct result of the innovativeness and tenacity of our founder and chairman, Mr. Charlie Aniceto V. Gorayeb. His expertise in the construction industry combined with his patience, hard work, and wholehearted dedication to Concrete Ventures Group, Inc. has been proven effective since our founding in 1990.

Local Manufacturing. Up to 50,000 linear meters a month.





c-joist™ Configurations

C-Joist is a precast and prestressed concrete joist designed as an alternative product to floor and roof slab systems. It has a compressive strength of 5,500psi and is equipped with pre-tensioned tendons as reinforcements to support longer spans.

C-Joist Type 101 has 2-sets of 7-wire, high tensile strength, prestressed wires used for light loads of short to long spans.

(e.g., residential and light commercial)


C-Joist Type 201 has 3-sets of 7-wire, high tensile strength, prestressed wires used for heavier loads of mid to longer spans.

(e.g., commercial, heavy residential, institutional, government/public buildings)


C-Joist Type 301 has 4-sets of 7-wire, high tensile strength, prestressed wires used for heavy loads of 6-6.5m in span.

(e.g., heavy commercial, industrial loading, essential facilities)


^{Type} 101



^{Type} 201



^{Type} 301




Three products. One brand.


C-Joist's structural forms are made to provide the structure with the sufficient amount of strength specified for its structural requirements and client needs.

- C-Joist with Removable Steel Form (RSF) has been sought out by various clients
- because of its appealing form. When shown exposed in interior spaces, its rounded alcoves provide subtle gradients from the light bouncing off it.
- C-Joist Permanent Concrete Form (PCF) is the most basic of all the products. Its
- straight and geometric shape makes it ideal for designs or buildings that offer the same character.
- C-Joist Structural Concrete Form (SCF) is made to enhance the C-Joist PCF. SY^2+Associates Inc., a structural engineering firm, designed the C-Joist SCF to act not only as a fixed form but also as a structural component. Making it a well-integrated part of the whole system.






C-JOIST.




C-JOIST_™ SCF



Designed for uniformity. Manufactured for efficiency.

The C-Joist Cutting List was developed years ago to standardize the dimensions and details required in building the joist components consistently and efficiently. Through our Cutting List Form, drawings done by our customers are sent to our Engineering Department for approval and/or corrections. Once complete, the final list is then set for fabrication. This method saves time and enables our joists to be delivered faster.




Flexible configurations. Different building types.



Throughout the years, we have provided support and cost-effective construction solutions for a wide range of building types. We offer value-engineering support during the schematic stage and installation support during construction to ensure optimum results.

	Mass housing
	Socialized housing
	High end housing Townhouses
Residential	Privately-owned residences
	Commercial buildings
	Mall buildings
NAP - LILE	
Mixed-Use	
& Commercial	
& Commercial	High-rise buildings
	Government
	Private schools
Public & Private	Municipal buildings
	Hospitals
Institutions	Churches
	Light and Heavy warehouses
	Factories
	Car parking
	Stadium
	Gymnasiums
Industrial	Cockpit arena
9 Assembly	Amusement park
a Assembly	Agricultural farm buildings
Mixed-Use & Commercial Public & Private Institutions Industrial & Assembly	Commercial buildings Mall buildings Condominiums Walk-up buildings Medium-rise High-rise buildings Government Private schools Municipal buildings Hospitals Churches Light and Heavy warehouses Factories Car parking Stadium Gymnasiums Cockpit arena Amusement park



C-Joist with Removable Steel Form (RSF) has been sought out by various clients because of its appealing form. When shown exposed in interior spaces, its rounded alcoves provide subtle gradients from the light bouncing off it.


Spacing Options

620 mm



900 mm







Technical Information


Total Dead Load 1900 Pa (41 psf)

Volume of Concrete Slab	0.085 m ³
Weight of Steel Reinforcement	4.50 kg/sq.m
C-Joist per linear meter	1.62 lm
C-Joist RSF per linear meter	1.50 pieces
Steel Stiffener per linear meter	4.50 pieces
Steel Stiffener per linear meter	4.50 pieces

Ultimate Moment Capacity (Kn-m)









C-Joist Permanent Concrete Form (PCF) is the most basic of all the products. Its straight and geometric shape makes it ideal for designs or buildings that offer the same character.

Dimensions (mm)





Technical Information

Total Dead Load 2200 Pa (46 psf) Volume of Concrete Slab

0.085 m³

Weight of Steel Reinforcement

C-Joist per linear meter

C-Joist PCF per linear meter


5 pieces


Weight of C-Joist PCF

7.5 kg/piece

Ultimate Moment Capacity (Kn-m)









c-JOIST_M

C-Joist Structural Concrete Form (SCF) is made to enhance the C-Joist PCF. SY^2+Associates Inc., a structural engineering firm, designed the C-Joist SCF to act not only as a fixed form but also as a structural component. Making it a well-integrated part of the whole system.

Dimensions (mm)







Technical Information

Total Dead Load	Slab	41.00 psf
3112 Pa (65 psf)	Partition	6.28 psf
()	Ceiling	5.00 psf
	Floor Finish	13.00 psf
	Miscellaneous	1.00 psf

Ultimate Moment Capacity (Kn-m)








Sample Comparative Analysis using ETABS - Beam Reinforcement

C-JOIST°

2nd Floor Beam Reinforcements using C-Joist




Parameters:

Distance from Faultline = 2km Soil Type = A Importance Factor = 1 LL = 4.8 kPa DL = 2.4 kPa 5 storeys at 3m per floor 14.88m x 12m

Parameters apply to all images that are under the Sample Comparative Analysis

Conventional Method

2nd Floor Beam Reinforcements using Conventional Method



As shown in the drawings, the required beam reinforcements using C-Joist (on the left) is lesser as compared to the required beam reinforcements for conventional construction.

Sample Comparative Analysis using ETABS - Column Reinforcement

C-JOIST[®]

Column Reinforcements using C-Joist

	\leq		\geq	2)			2)			2)	
	425	137	425	456	147	456	425	137	425		_RD
	405	518	365	333	476	333	365	518	405		
1600			1600			1600			1600		
	580	185	446	510	164	510	446	185	580		_ 5th Floor
	376	425	331	332	422	332	331	425	376		
1600			1600			1600			1600		
	720	228	632	660	210	660	632	228	720		_ 4th Floor
	425	425	425	425	419	425	425	425	425		
1600			1600			1600			1600		
	843	264	779	769	242	769	779	264	843		_ 3rd Floor
	552	425	480	441	418	441	480	425	552		
1600			1600			1600			1600		
	809	260	829	762	240	762	829	260	809		_ 2nd Floor
	598	425	476	425	413	425	476	425	598		
1929	Χ		2464			2464			1929		
							<u></u>				_ Ground Floor

Conventional Method

Column Reinforcements using Conventional Method

(2				2			2			2	
$\left(A\right)$			(E	3)		([]	\supset	
	425	142	439	476	153	476	439	142	425		RD
	425	535	374	326	469	326	374	535	425		
1600			1600			1600			1600		
	729	230	573	640	204	640	573	230	729		_5th Floor
	425	507	374	414	472	414	374	507	425		
1600			1600			1600			1600		
	870	272	765	794	250	794	765	272	870		_ 4th Floor
	425	513	425	425	469	425	425	513	425		
1600			1600			1600			1600		
	994	307	920	905	282	905	920	307	994		_3rd Floor
	513	511	446	432	468	432	446	511	513		
1600			1822			1822			1600		
	945	302	974	899	280	899	974	302	945		_ 2nd Floor
	554	516	463	429	464	429	463	516	554		
2334			3170			3170			2334		
							<u> </u>				_ Ground Floor

As shown in the drawings, the required column reinforcements using C-Joist (on the left) is lesser as compared to the required column reinforcements for conventional construction.



Speeds up construction. Eliminates formworks and scaffoldings. Cost Effective.





The modular nature of the C-JOIST system reduces the amount of time spent on installation, concrete slab pouring, and the dismantling of materials.



Greatly reduce or totally eliminate the need for formworks and scaffoldings giving workers a spacious and orderly workspace for efficient mobilization.




Save up to 20-25% on slab cost. In addition, the integration of the C-JOIST system during the design stage will result to lesser columns and beams due to longer spans.


FREE STRUCTURAL DESIGN

Connection Details


C-Joist on Top of Beam




C-Joist on Steel I-Beam



C-Joist Integrated with Beam



C-Joist on Corbel Type Beam



Key Guidelines

Handling	 C-Joist can be hand-carried or hoisted Pick-up points are 1/5 from both ends If hand-carried, always lift C-Joist in an upright position
	d. All bearings and another and another and another
Bearing	All bearing surfaces must be true to line and grade C-Joist must be installed with 100mm minimum bearing on
	concrete and 75mm minimum bearing on steel
Safety	Removable steel forms are only used to support the concrete during pouring. For safety, it is recommended to walk on C-Joist
Shoring	C-Joist must rest firmly before pouring concrete slab
	Shoring members must be capable of supporting the dead weight
	of C-Joist and concrete slab:
	■ Quarter Spacing
	For C-Joist more than 5.00m in span
	Mid-span Shoring For C-Joist above 3.00m to 5.00m in span
	No Shoring For C-Joist below 3.00m in span

Installation Process

- Step 1 Arrange C-Joists onto their designated area/s and space them as specified.
- Step 2 Mount either PCF, RSF, or SCF components on top of C-Joist's shoulder and lay them per piece--starting from the interior face of the beam. If RSF is used, steel stiffeners are placed underneath to temporarily lock and support the steel forms.
- **Step 3** Provide shoring as needed. Read 'Key Guidelines' for spacing information.
- Step 4 Anchor components with dowel bars parallel to the C-Joist layout to serve as shear connectors. Spacing depends on the span of the joist with bars bent at either L/3 or L/4.
- Step 5 Reinforce the slab with a 6mm diameter welded wire mesh at 150mm square opening. Use appropriate lapping methods to ensure the mesh is secured properly.
- Step 6 Pour concrete with at least 3,000psi compressive strength after 28-days. Slab thickness can range from 50mm to 75mm.






















Contact any of our branch offices.

Corporate Information

The C-Joist Floor and Roof Slab System is produced by Concrete Ventures Group, Inc. For three decades, we have been providing pre-cast concrete joists to various architects, engineers, builders, and developers. Our manufacturing plant is located in Malvar, Batangas and it is where we produce our joists of unmatched quality in the Philippines. For inquiries, contact any of our branch offices.

	CVG Centre, 36 First Avenue, Cubao, Quezon City, 1111 Philippines
Sales Office	t: (02) 8723 4922 / (02) 8725 3953 m: 0968 850 2055 / 0928 517 3987 0920 928 6426 / 0920 928 6426 f: (02) 8723 4920 e: contact@c-joist.com
	Sitio Kap. Maria, Brgy San Pioquinto, Malvar, Batangas City
Manufacturing Office	t: (043) 740 6432 f: (043) 778 4536
	Ar. Glen Paul B. Celo 51 Rodriguez Ave., Brgy. 36, Bacolod City, Negros Occidental
Bacolod Branch	t: (034) 446 7695 m: 0939 917 7569 / 0917 527 0234 e: celo_glenpaul@yahoo.com feds_construction@yahoo.com
	Ar. Rolando G. Abarquez Hacienda Mandaue Road Highway Maguikay, Mandaue City, Cebu
Cebu Branch	t: (032) 344 6207 f: (032) 346 2615 m: 0905 399 4548 / 0917 779 2455 / 0922 871 1339 e: a_bar_keys@yahoo.com
	Engr. Nielson P. Allam 17 Democracia Street, Jaro, Iloilo City
Iloilo Branch	t: (033) 329 7477 m: 0922 826 0125 / 0908 889 1245 e: jcmnconstruction@yahoo.com nielsonallam@yahoo.com



